## AMENDMENTS TO THE CLAIMS

This listing will replace all prior versions, and listings, of claims, in the application:

## Listing of claims:

(currently amended) An abrasive cleaning <del>plant apparatus</del> comprising:
 a single-block plastic blasting booth (C) having a front wall, a rear wall, a top wall, a bottom wall, and side walls.

wherein the front wall, the rear wall, the top wall, the bottom wall, and the side walls are molded to form a single component in plastic material,

wherein at least a portion of one of the side-walls comprises an opening is openable by rotationcloscable by a door rotatable on a hinge that connects the single-block-blasting booth with the openable side wall portiondoor, thereby the opening providing access inside the single-block to the interior of the blasting booth, and

wherein one or more gaskets create a hermetic seal between the single block blasting booth and the openable side wall portiondoor, the one or more gaskets being provided on one or more of the single-block blasting booth and of the openable side wall portionopening and the door.

2-3. (canceled)

4. (currently amended) The abrasive cleaning plant-apparatus according to claim 1, wherein at least a portion of the front wall (Ca) is sloped.

wherein an inspection window (Cf) comprising a transparent surface is provided in the front wall, and

Application S/N 10/537,207 Reply to Office Action of 06/16/2006 Amendment Dated 10/12/2006

wherein two holes (Cm) are provided in the front wall, the two holes being positioned side by side and being structured for having a work glove extending from each of the two holes.

5-6. (canceled)

7. (currently amended) The abrasive cleaning plant apparatus according to claim 1, wherein one or more of the walls (Cp) of the single block blasting booth comprise two plastic sheets substantially parallel to each other and joined along the edges to form a closed hollow box-shaped structure.

8. (currently amended) The abrasive cleaning plant apparatus according to claim 7, wherein an insulating material is provided between the two plastic sheets.

9-13 (canceled)

14. (currently amended) The abrasive cleaning <del>plant apparatus</del> according to claim 1, wherein the bottom wall <del>(Ct)</del> is shaped like a hopper and is connected to an outlet pipe <del>(Ce)</del>.

15. (currently amended) The abrasive plant apparatus according to claim 14, further comprising a support structure (S) for the single-block-blasting booth-(C), a feeding device (A) providing a granular blasting material to the single-block-blasting booth, and a plastic filtering device (F) filtering the blasting material exiting the single-block-blasting booth, the filtering device (F) being integrated within the single-block-in flow communication with the blasting booth-(C).

16. (currently amended) The abrasive cleaning <del>plant apparatus</del> according to claim
15.

wherein the support structure (S) is box-shaped and open on one side (Ss) to accommodate the hopper-shaped bottom wall (Ct) of the sandblasting-blasting booth, and Application S/N 10/537,207 Reply to Office Action of 06/16/2006 Amendment Dated 10/12/2006

wherein a side wall of the support structure (S) is provided with an opening (Sf) facing the filtering device (F) and enabling a connection of the outlet pipe (Ce) with the filtering device (F).

- 17. (currently amended) The abrasive cleaning plant apparatus according to claim
  15, wherein the feeding device (A) emprises is housed in a shell structure (Ai) having a size and a profile adequate to provide a lateral coupling of the feeding device with the single block-be coupled with one side wall of the blasting booth-(C).
- 18. (currently amended) The abrasive cleaning <a href="https://plantage.cording.com/https://plantage.cording.cordi
- 19. (currently amended) The abrasive cleaning <a href="mailto:plant-apparatus">plant-apparatus</a> according to claim 18, wherein the means for delivering the blasting material are connected to the tank with a tubular structure having a nozzle at the end opposite to the tank.
- 20. (currently amended) The abrasive cleaning plant apparatus according to claim 15, wherein the support structure (S), the feeding device (A), and the filtering device (F) are contained within a single L-shaped element
- 21. (currently amended) The abrasive cleaning plant apparatus according to claim 15, wherein the filtering device (F) is housed within a filtering shell structure (Fi), and wherein the filtering device (F) comprises a suction device (Fa) providing an exit flow of gases from the filtering device (F), and a cartridge filter (Fe) connected to the suction device (Fa).
- 22. (new) The abrasive cleaning apparatus according to claim 18, wherein the blasting material comprises sodium bicarbonate or a mixture of granular elements comprising sodium bicarbonate.